6 Industrial Park Drive
Wheeling, WV 26003
Glass Sales (800) 777-6919
Aluminum Sales (888) 991-2200
FAX (800) 288-6919

www.wawilsonglass.com

WA Wilson produces insulating glass under the trade name StarLite.

As a licensee in the Insulating Glass Certification Council (IGCC), our product is certified using anodized aluminum spacers according to ASTM E2190 (formerly E773 and E774) standards.

The Profilglass anodized aluminum spacers are filled with molecular sieve desiccant, bent and joined with Lisec equipment creating StarLite's dual-seal hermetically dehydrated air space construction.

The primary insulating unit seal is polyisobutylene (PIB), and the secondary seal consists of GE IGS3723 two-part silicone.

WA Wilson seeks to maintain overall insulated unit thickness of +/- 1/16".

Starlite units carry a ten-year warranty against seal failure in most applications. A copy of our warranty is attached.

WA Wilson produces Heat Treated glass under the trade name TempRite that meets the requirements of:

ASTM C1036 Standard Specification for Flat Glass

ASTM C1048 Standard Specification for Heat Treated Glass

ANSI Z97.1 American National Standard for Safety Glazing Materials used in Buildings

16 CFR 1201 Category II Consumer Products Safety Commission Council (SGCC)