HIGH QUALITY GLASS DOORS FEATURING OUR NEW GLASS DOOR RAIL SYSTEM WITH MATCHING SIDELITE RAILS AND ROLL-IN GASKET

The Unique

The Unique Wedge-Lock Clamps the Glass Securely, yet Removes Easily Tempered bolts draw the tapered clamp jaws downward against the internal wedge design of the rail body, resulting in very high gripping pressure along the entire edge of the glass.

*National Technical Systems tested the Wedge-Lock Door Rail System at a temperature range from -10°F to 150°F, with 1000 pounds of tension load applied. No evidence of movement was detected at any temperature. At ambient temperature, in a "Pull-To-Failure Test", 7000 pounds of tension was required before any creep (not failure) was detected. *Certified Laboratory


COVERING THE
ENTIRE SPECTRUM
OF DOORS WITH
4", 6" AND 10"
RAILS IN FIVE
BEAUTIFUL
STOCK FINISHES

The new Wedge-Lock Door Rail System provides the fastest fabrication and installation. Experienced installers can now secure a door rail in less than ten minutes. After rail installation to the glass, all that is needed before hanging the door is attachment of the appropriate arm or pivot to the unique, pre-installed adjustable slideblock. This standard feature on both bottom and top rails allows for door alignment without removing the door.

Wedge-Lock Securing Door Rails are available in five stock finishes in single and double door styles, and accept 3/8" (10 mm) or 1/2" (12 mm) glass. By using the New Wedge-Lock Door Rail System, glass professionals can simplify the ordering process, cut inventory in half, and speed the installation process.



Heavy Glass Sliding Door System also Available



Fabrication, Installation, Adjustment, even Repair is Easy. Adjusts Simply without having to Remove the Door.







Complementary Sidelite Rails, Headers, Door Closers, Handles and Locks are also available. Standard finishes include Brushed Stainless Steel, Polished Stainless Steel, Polished Brass, Duranodic Bronze, and Clear Anodized. Custom finishes are also available on special order.



NEW

• Available in Polished or Brushed Stainless Steel • Can Be Used as a Replacement for Older Panics

• Dogging Feature Defeats Locking Action During Business Hours • Custom Sizes Ship Within Two Weeks

Our New CRL Glass Door Panic and Deadbolt Handles are designed to allow maximum view and a contemporary look to 1/2" (12 mm) or 3/4" (19 mm) tempered glass doors. Installations can be made on single or double doors. They are ready to be installed on 36" to 48" wide doors ranging from 90" to 102" high without modifications. "Dogging", locking the device in the open position, is easy with just a slide of a knob.

17830 West Valley Highway, Seattle, WA 98188 PH: (425) 656-2626 • (800) 552-2227 • FAX: (425) 656-2601